

04-12-01

A

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

Robert K. Rowe et al.

Serial No.: Unknown

Examiner: Unknown

Filing Date: April 11, 2001

Group Art Unit: Unknown

For: ENCODED VARIABLE FILTER SPECTROMETER

Docket No.: 1023.1123101

TRANSMITTAL SHEET

The Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

CERTIFICATE UNDER 37 C.F.R. 1.10: The undersigned hereby certifies that this paper or papers, as described herein, are being deposited in the United States Postal Service, "Express Mail Post Office to Addressee" having an Express Mail mailing label number of: EL837557669US, in an envelope addressed to: Assistant Commissioner for Patents, Washington, D.C., 20231 on this 11th day of April, 2001.

By Kathleen L. Boekley
Kathleen L. Boekley

We are transmitting herewith the attached Patent Application including the following:

- ☒ FORTY-FOUR (44) sheet(s) of specification.
- ☒ SIXTY-TWO (62) claim(s).
- ☒ ONE (1) sheet(s) of Abstract.
- ☒ FIFTEEN (15) sheet(s) of informal drawings.
- ☒ Unexecuted Declaration and Power of Attorney.
- ☐ A verified statement(s) to establish small entity status under 37 C.F.R. 1.9 and/or 1.27 is enclosed.
- ☐ An Assignment of the invention to _____ is being filed contemporaneous with this patent application.
- ☐ A certified copy of a _____ application, serial no. _____, filed _____, 19____, the right of priority of which is claimed under 35 U.S.C. 119.


CLAIMS AS FILED						
	(1)	(2)	SMALL ENTITY		OTHER	
FOR:	# FILED	# EXTRA	Rate	Fee	Rate	Fee
BASIC FEE	1	0		\$355		\$710
TOTAL CLAIMS	62-20 =	42	X9=	\$	X18=	\$756
INDEPENDENT CLAIMS	6-3 =	3	X40=	\$	X80=	\$240
() MULTIPLE DEPENDENT CLAIM PRESENTED			+135=	\$	+270=	\$0
TOTAL			\$		\$1,706	

*If the difference in Column (1) is less than zero, enter "0" in Column 2.

[] Other _____.

[XX] A check in the amount of \$1,706.00 is enclosed.

[XXX] Please charge any deficiencies or credit any overpayment in the enclosed fees to Deposit Account No. 50-0413.

By: 
David M. Crompton

Reg. No. 36,772

David M. Crompton
CROMPTON, SEAGER & TUFTE, LLC
331 Second Avenue South, Suite 895
Minneapolis, Minnesota 55401-2246
Telephone: (612) 677-9050
Facsimile: (612) 359-9349

ENCODED VARIABLE FILTER SPECTROMETER

Related Applications

This application is related to U.S. Patent Application Serial No. _____, entitled "System for Non-Invasive Measurement of Glucose in Humans"; U.S. Patent Application Serial No. _____, entitled "Illumination Device and Method for Spectroscopic Analysis"; and U.S. Patent Application Serial No. _____, entitled "Optically Similar Reference Samples and Related Methods for Multivariate Calibration Models Used in Optical Spectroscopy", all filed on the same date herewith and assigned to the assignee of the present application. The disclosure of each of these related applications is hereby incorporated by reference.

Field of the Invention

The present invention generally relates to optical spectrometers. More specifically, the present invention relates to encoded filter-based optical spectrometers.

Background of the Invention

Optical spectrometers are systems that permit the measurement of optical intensity at specific wavelengths within a spectral region. In broad terms, a spectrometer can either measure each of the wavelengths individually, or it can measure multiple portions of the spectrum at one time. In the first case, the spectrometer operates in a sequential mode and is referred to as a scanning spectrometer system. In the latter case, the spectrometer is said to operate in a multiplexed fashion. Multiplexed spectrometers can be further divided into those that are based upon a detector array and those that use just a single detector. Array-based spectrometers incorporate some optical element such as a grating or prism to separate the light and distribute it across the detector array to record the individual intensities incident

on the detector pixels. In contrast, a single-element multiplexing spectrometer incorporates an optical encoding subsystem such as an interferometer to encode the light in a manner that the resulting signal can be processed after collection to regenerate the individual spectral intensities. The subject of this disclosure is a new method for constructing a multiplexing spectrometer that is based on a single element detector, an optical filter assembly, and an encoding mask.

Spectroscopic measurement systems operating in the visible or near-infrared spectral regions may be used to measure a wide variety of sample characteristics that convey information regarding the presence and/or quantity of analytes. In particular, they can be used to measure analytes in inanimate samples, biological samples, and in human subjects. They can provide identifying information about the person or other sample type, provide information about the age, gender, or other demographic factors about the person being measured, provide information about the disease state of the person or sample being measured, or provide information about the quality or similarity of the sample being measured relative to some known population. In order to design and build a commercially viable spectroscopic system for these types of measurements, the spectrometer should be multiplexed and have high optical throughput in order to allow the spectroscopic system to collect as much light as possible in a given measurement time, and thereby increase the total measurement signal-to-noise ratio. The spectrometer system should also be stable to reduce the effect of instrument drift and reduce noise. Also, in order to facilitate the ability to perform a calibration on one instrument and use the same calibration model for other similar instruments (i.e. calibration transfer), the spectrometer system should be of a simple and

robust design with a minimum number of components that have critical dimensions or require precise movement.

In addition, in order to facilitate efficient manufacture of such a spectrometer, it should contain few parts with a minimal number of adjustable critical dimensions. Ideally, the parts of the spectrometer would be well suited for large-scale manufacturing processes in order to fulfill the demands of large-volume production. It is also desirable that the parts of the spectrometer are manufactured using well-developed and well-understood technologies and materials to avoid unexpected interactions and effects when the parts are assembled into a complete spectrometer.

For broad commercial viability, the spectrometer should be designed to be as small and as inexpensive as possible. Due to the high cost of near-infrared detector arrays, a near-infrared spectrometer suitable for low-cost applications preferably will be based upon a single-element detector. In addition, the spectroscopic system must be rugged to withstand shock, dust, humidity and other adverse environmental influences.

There is a variety of spectrometers capable of being incorporated in a spectroscopic system to produce optical spectra which potentially can be used for analysis of analytes in biological media. Examples of suitable spectrometers include: diffraction spectrometers utilizing scanned or array diffraction gratings; refraction spectrometers utilizing a prism or mock interferometer; interference spectrometers utilizing a scanning Fourier Transform interferometer or stationary interferometer (e.g., Sagnac interferometer as described by Rafert, et al., Monolithic Fourier-Transform Imaging Spectrometer, Applied Optics, 34(31), pp 7228-30, 1995.); discrete light source spectrometers utilizing light emitting diodes, laser diodes or tunable diode lasers; and filter-based spectrometers utilizing acousto-optical

transmission filters, liquid crystal filters, discrete optical filters, linear variable filters, or circular variable filters.

While each of these spectrometers is viable for generating spectra, each has shortcomings in terms of either optical throughput, stability, versatility, availability, size, or cost, depending upon the application. For example, in the case of using near-infrared spectra (1.25 – 2.5 μ m) to measure analytes in biological media, Fourier Transform instruments that provide high optical throughput, high stability, high versatility and are readily available tend to be large and relatively expensive. While design improvements can be made to reduce size and cost while maintaining the other desirable characteristics of an FTIR system for this application, other methods for generating spectra with fewer, less costly parts could be competitive with the FTIR approach.

One such alternative is the use of optical filters. There are commercially available assemblies for spectral separation and detection that use optical filters, such as the MicroPac assembly available from Optical Coating Laboratories, Inc. (OCLI), as schematically shown in Figure 1. The MicroPac assembly receives light or radiation through a dielectric linear variable filter (LVF) 14, micro-optics 16 and a detector array 18. The LVF 14 is a bandpass dielectric filter whose properties vary over its length such that the central wavelength of the pass band varies linearly across the filter 14. OCLI's MicroPac assembly images the LVF 14 onto the detector array 18 to generate a spectrum of the light incident on the LVF 14. The cost of the MicroPac assembly that can be used for visible and/or very near infrared regions is significantly affected by the price of the particular silicon detector array utilized. Due to the relative scarcity and

high cost of NIR arrays that can detect light with a wavelength as long as $2.5\mu\text{m}$ (e.g., InGaAs or PbS), the NIR embodiment of the OCLI MicroPac assembly is expensive.

During the proceedings of the MicroPac Conference hosted by OCLI in California, on May 11th and 12th, 2000, Shroder proposed the use of a fiber optic coupling to increase efficiencies of the assembly 10 by twenty (20) to forty (40) times. See Current Performance Results by Robert Shroder, MicroPac Forum Presentation, May 11, 2000. However, in all instances, the OCLI assembly 10 is used on the detector side of a spectrometer just prior to the detector array. It has not been suggested to use the LVF 14 on the illumination side of the system, prior to the sample under analysis, nor has it been suggested to include the LVF with an integrating chamber for coupling a light source to an encoded filter-based spectrometer.

Another approach used in spectrographic analysis is to incorporate a Hadamard or other encoding mechanism in a spectrometer to enable multiplexing and thereby increase the overall optical throughput of the system, as is known in the art. For example, Harwitt and Sloan (Harwit, M. and N. Sloan, Hadamard Transform Optics, pages 109-145, Academic Press, 1979) discuss the application of a Hadamard mask to either or both the entrance and exit planes of a grating spectrometer. However, such prior art does not indicate that the encoding can be combined favorably with a filter-based instrument.

U.S. Patent No. 6,031,609, entitled "Fourier Transform Spectrometer using a Multielement Liquid Crystal Display," teaches a system and method for combining prisms or gratings with a liquid crystal spatial light modulator in such a way as to create a Fourier Transform spectrometer. The advantages claimed for this system include increased signal-to-noise ratios over scanning dispersive instruments for a fixed integration time without any

moving parts. However, such prior art does not indicate that multiple encoding methods and systems can be applied for encoding, or that the encoding can be combined favorably with a filter-based instrument.

From the foregoing, it should be apparent that there is an unmet need for an
5 encoded filter-based spectrometer that optimizes optical throughput, stability, versatility, availability, size, and cost.

Summary of the Invention

The present invention provides a spectrometer capable of being incorporated into a small, simple, rugged, inexpensive spectroscopic system for commercial applications. The
10 spectrometer of the present invention optimizes optical throughput, increases the signal-to-noise ratio of the system, and decreases the complexity of the system. The spectrometer of the present invention is well suited for incorporation in a spectroscopic system that collects data necessary to perform spectroscopic determinations on biological media. Spectroscopic determinations include measuring the quantity of an analyte, the presence or absence of an
15 analyte, checking for sample quality and consistency with a known class of samples, performing classification of disease states, estimation of age and gender, and establishing identity via individual spectroscopic markers. Biological media includes living tissue, excised tissue, and fluids measured either in-vivo or in-vitro derived from humans, animals and other living organisms. Any of these spectroscopic measurements can be made using
20 either diffuse reflectance or transmission measurement optical sampling geometries.

The present invention provides a number of different spectrometers for use in spectroscopic systems. The spectroscopic systems of the present invention basically include a light source for generating light and a detector for receiving light. The light

source can include a multiwavelength tungsten-halogen emitter, an array of LED infrared emitters, a flashlamp, an arc lamp or any other illumination source. Each spectrometer configuration also preferably includes a means to encode the light emitted by the source. As well, each spectrometer also preferably includes a single or multiple variable optical bandpass filter(s) with properties that vary with position, such as a linear variable filter (LVF), or an optical filter assembly that includes a number of discrete filters with two or more different optical bandpass regions for receiving and filtering light from the source. Light that strikes the filter within the bandpass region is transmitted through the filter over a specific area or region, and the light outside the bandpass region is substantially reflected back.

In addition, each spectrometer may include an integrating chamber that collects and redirects light that is emitted from the source and does not pass through the filter. The integrating chamber essentially boosts the optical throughput of the spectroscopic system and increases the signal-to-noise ratio. The integrating chamber may allow direct illumination of the filter from the light source and also allows the light reflected back from the filter to make additional attempts to pass through the filter. The integrating chamber maximizes the return of the reflected light to the filter assembly and minimizes optical losses. By increasing the optical throughput and minimizing optical losses, the spectrometer may be arranged in the spectroscopic system such that the sample is disposed adjacent to either the detector or the light source.

The light source may be positioned inside or outside the integrating chamber. If the light source is located outside the integrating chamber, the integrating chamber may be of an orthogonal design (i.e., cuboid or cylindrical) to preserve the optical geometric

characteristics of the light entering the integrator, even after multiple reflections from the filter. This is beneficial if it is necessary to maintain the angular distribution of the light entering into any of the subsequent optical components of the spectrometer system. Alternatively, a round, polygonal, conical or irregular shape may be used if it is desired to homogenize the light from the source. Further, the integrator may have at least a portion that is shaped to focus light over a desired specific area.

The bandpass filter may be selected and adjusted to optimize light throughput in the system. Aspects of the system that can be optimized by the choice of the variable filter or filter assembly include maximizing the amount of light in spectral regions important to the measurement being made, reducing photon noise by eliminating light in spectral regions outside the band(s) of interest, and optimizing the spectral properties of the light passing through the tissue or other sample type to reduce or eliminate optically induced damage to the sample. The filter may comprise a variable filter or a selection of discrete bandpass filters. In addition, the filter may comprise a linear or non-linear variable filter.

The output of a linear variable filter is generally distributed spatially over a relatively large area. In one embodiment, a first integrating chamber is used to receive light from the source and passes this light to a first linear variable filter. Light passing through the appropriate bandpass of the linear variable filter then passes to an encoding unit. Light exiting the encoding unit strikes a second linear variable filter having a spatial distribution of wavelength passbands matching those of the first linear variable filter. Light passing through the appropriate portion of the second linear variable filter enters a second integrating chamber which allows light from the large linear variable filter surface area to be efficiently collected into a smaller exit port. This allows for a dramatic

reduction in the size of the fiber optic bundle and/or detector which would otherwise receive the light exiting the relatively large surface area of the linear variable filter.

The encoding unit is a spatial light modulator that may comprise a movable (linear or rotating) mask having an aperture array, a liquid crystal spatial light modulator, a micro-electromechanical system (MEMS), a digital mirror device (DMD) or any other equivalent method for spatial modulation of the light. In addition, the filter and the encoding unit may be combined into a single unit.

Brief Description of the Drawings

Figure 1 is a schematic illustration of the MicroPac assembly;

Figure 2 is a schematic illustration of a spectrometer system utilizing a basic encoded variable filter device in accordance with an embodiment of the present invention;

Figure 3 is a graph comparing linear and non-linear variable filters;

Figure 4 is a schematic illustration of a spectrometer system utilizing an external source interfaced with imaging optics in accordance with an embodiment of the present invention;

Figure 5 is a schematic illustration of a spectrometer system utilizing an external source interfaced with non-imaging optics in accordance with an embodiment of the present invention;

Figure 6 is a schematic illustration of a spectrometer system utilizing a rotating mask encoding system in accordance with an embodiment of the present invention;

Figure 7 is a schematic illustration of a spectrometer system utilizing a rotating circular variable filter (CVF) encoding system in accordance with an embodiment of the

present invention;

Figure 8 is a schematic illustration of a spectrometer system utilizing a liquid crystal encoding system in accordance with an embodiment of the present invention;

Figure 9 is a schematic illustration of a spectrometer system utilizing a digital mirror device (DMD) encoding system in accordance with an embodiment of the present invention;

Figure 10 is a schematic illustration of a spectrometer system utilizing optical fibers with integral bandpass filters in accordance with an embodiment of the present invention;

Figure 11 is a schematic illustration of a spectrometer system utilizing a micro-electromechanical system (MEMS) encoding system in accordance with an embodiment of the present invention;

Figure 12 is a schematic illustration of a spectrometer system utilizing a MEMS-based spectral encoding unit in accordance with an embodiment of the present invention;

Figure 13 is a schematic illustration of a spectrometer system utilizing a MEMS-based double encoding system in accordance with an embodiment of the present invention;

Figure 14 is a schematic illustration of a spectrometer system utilizing an integrated non-fiber arrangement in accordance with an embodiment of the present invention; and

Figure 15 is a schematic illustration of a spectrometer system utilizing an input integrating chamber and linear variable filter passing light to a spatial encoder with light

exiting the encoder and striking a second linear variable filter and integrating chamber to allow for a smaller area collection bundle or detector.

Detailed Description of the Invention

The following detailed description should be read with reference to the drawings in which similar elements in different drawings are numbered the same. The drawings, which are not necessarily to scale, depict illustrative embodiments and are not intended to limit the scope of the invention.

Refer now to Figure 2, which is a schematic illustration of a spectrometer system 100 utilizing a basic encoded variable filter (EVF) device 111 in accordance with an embodiment of the present invention. Note that spectrometer components 106/108 are collectively referred to as encoded variable filter (EVF) device or unit 111. Further, component 104, the integrating chamber, is an optional component included in encoded variable filter device 111. The spectrometer 100, in a preferred embodiment, includes an optical light source 102, an optical integrating chamber 104, a filter assembly 106 such as a linear variable optical bandpass filter, a spatial encoding device 108, a sampler 112 incorporating illumination optical fibers 110 that shine light into the tissue at the sampler/tissue interface 114 and detection optical fibers 116 that detect light after passing through the tissue (in either reflectance or transmission), a lens 118, a detector 120, and a computer 122 to control the spatial encoding unit 108 and to collect the detected optical signal from the detector 120. The computer 122 includes the basic components of a processor, a memory for storing data and software, an input device and an output device.

As shown, the spectrometer system 100 is arranged with the sampler 112 and sample interface 114 between the spectrometer components 102-110 and the detector 120

(source-spectrometer-sample-detector). Those skilled in the art will recognize that all embodiments described herein may be arranged with the sampler 112 and sample interface 114 between the light source 102 and the spectrometer components 104-120 (source-sample-spectrometer-detector). The illustrated configuration (source-spectrometer-sample-detector) of the system 100 is especially suitable for diffuse reflectance tissue sampling due to the highly attenuating nature of the tissue. In the near infrared, one watt of light incident on the tissue will yield between 1 and 100 micro-watts of light that is available for detection (the exact ratio depends upon the wavelength, the exact sampler geometry, and other factors). Due to the large optical losses caused by attenuation and scatter by tissue, it is advantageous to minimize instrumental losses between the exiting light at the tissue interface 114 and the detector 120. Thus, placing the spectrometer components 102-110 prior to the sampler 112 and sample interface 114 removes a potentially large loss in the detection channel. The illustrated configuration of the system 100 is optimal if the illumination source 102 and spectrometer components 106/108 can produce enough optical power such that the sample (e.g., skin tissue) can be illuminated at a level below the sample damage threshold.

In a preferred embodiment, the optical filter assembly 106 is constructed from one or more dielectric filters in such a way that light that is not passed through the filter is substantially reflected. In this preferred embodiment, the optical integrator or integrating chamber 104 is incorporated in the EVF unit 111 to take advantage of the dielectric optical filter 106 which, over its surface area, includes regions which transmit light with a single, well-defined band of optical wavelengths. With the dielectric filter 106, light outside the bandpass region in a specific portion of the surface area is substantially

reflected and would represent a significant optical loss but for the integrating chamber 104. In the present invention, the integrating chamber 104 is used to capture and redirect the light that is outside the bandpass region of a portion of the filter 106 to other portions of the filter appropriate for the wavelength region, resulting in a significant increase in
5 the optical power passing through the filter 106.

The integrating chamber 104 comprises a hollow shell 103 defining an interior 105. The inside surface of the shell 103 comprises a reflective material or coating such that light entering the interior 105 is reflected off of the inside surface of the shell 103 until the light exits the integrating chamber 104. Alternatively, the integrating chamber
10 104 can be a light-transmitting solid, such as glass or a liquid-filled chamber, each with a reflective surface 103. The reflective surface(s) of the integrating chamber may be optically smooth, providing specular reflections, or optically rough, providing diffuse reflections. To preserve angular characteristics of the light, the reflective surfaces of the integrating chamber 104 may be made optically smooth and the shell may be of
15 orthogonal design. Orthogonal design means that the walls of the integrating chamber 104 are orthogonal to the filter 106 and encoding unit 108 (i.e., cuboid or cylindrical integrating chamber), although other shapes (e.g., spherical, oblong, etc.) are also feasible. The light source can also be placed within the integrating chamber 104. Further, an integral unit could be used wherein the glass envelope holding the bulb
20 filament is designed as an integrating chamber having the above features.

In a preferred embodiment, the optical integrator 104 may boost the optical throughput of the spectrometer system 100. The optical integrator 104 may allow light from the light source 102 to directly illuminate or strike the variable filter assembly 106 and also

allows the light rejected (i.e. reflected) from the variable filter assembly 106 or the spatial encoding unit 108 to make additional attempts to pass through the filter 106. The optical integrator 104 is designed to maximize the return of the reflected light to the filter assembly 106 with a minimum of optical losses. In addition, in cases where the light source 102 is
5 located outside of the integrating chamber 104, the integrating chamber 104 may be fabricated as a reflective cuboid, which will preserve the optical geometric characteristics of the light entering the integrator 104 even after multiple reflections from the filter 106 surface.

The optical light source 102, such as a quartz tungsten halogen lamp, may be
10 located inside the optical integrating chamber 104. Alternatively, the light source 102 may be located outside the optical integrating chamber 104, with all or a portion of the emitted optical radiation from the light source 102 directed into the integrating chamber 104 using lenses, mirrors or other optical means with substantially the same effect.

The dielectric bandpass filter assembly 106 may be made of a single linear
15 variable filter, two or more linear variable filters, a circular variable filter (or segment thereof), a variable filter embodying a nonlinear bandpass profile, or a plurality of individual optical bandpass filters fabricated as separate pieces. The optical filter(s) 106 may be dielectric and be positioned such that light that is not of the proper wavelength for transmission by a filter element (or a portion of the filter) is substantially reflected back
20 into the integrating chamber 104. In so doing, the reflected light can be redirected to impinge on a different filter element (or portion of the filter), thereby substantially increasing the optical throughput of the system 100. Other filters could also be utilized, including absorbance filters, metallic filters or tunable filters.

A variable optical filter 106 having a nonlinear bandpass profile may be utilized to pass more light of desirable wavelengths and less light of less desirable wavelengths. Figure 3 is a graph showing a representative distribution of multiple wavelength light passing through a linear and non-linear variable filter. The vertical axis is the position along the variable filter and graphically illustrates a design wherein a greater portion or area of the filter is devoted to passing light in spectral regions of more importance to the analysis. As an alternative, a plurality of discrete filter elements may be used to pass more light of desirable wavelengths and less light of less desirable wavelengths by selecting the appropriate number and type of bandpass filter elements (central wavelengths and optical widths). These filter elements can be arranged in a non-ordered or ordered arrangement as appropriate to other characteristics of the design or manufacture of the EVF unit. The dielectric filter(s) 106 may be positioned such that each distinct filter element is proximal to, or can be imaged onto, a different location of the spatial encoding unit 108.

One means of determining the configuration of a non-linear variable optical filter is to interrogate the final regression coefficients (FRC) of a spectroscopic system. Those wavelengths at which the FRC has a large absolute magnitude are the wavelengths that are most heavily weighted by the system to produce the analyte estimate. For this reason, the signal-to-noise at each of these strongly-weighted wavelength bands will have the greatest influence on the resulting prediction error. A non-linear filter can be used to adjust the distribution of light such that strongly FRC-weighted wavelength bands are given a larger spatial segment of the filter. In general, the incorporation of a new non-linear filter in a spectroscopic system will alter the resulting FRC. Therefore, if desired,

1 this new system and its corresponding FRC can then be the basis for a new non-linear
filter optimization. This iterative calculation of the non-linear filter design can then be
repeated as necessary to achieve the desired level of refinement. The use of an end-to-end
computer model of the system can be used to facilitate this iterative design process, rather
5 than relying on multiple hardware/experimental iterations.

The spatial encoding unit 108 comprises a spatial filter that encodes each physical
location on the optical bandpass filter(s) 106, which in turn corresponds to a different
optical frequency. The encoding unit 108 may utilize a Hadamard transform, a Fourier
amplitude modulation, a Fourier frequency modulation, a random coding pattern, or any
10 other similar variant. Devices suitable for this type of encoding unit 108 include
electromechanical aperture arrays (circular motion or linear), liquid crystal spatial light
modulators, micro-electromechanical systems (MEMS), digital mirror devices (DMDs)
also known as Digital Light Processors (DLPs), and others described in more detail
hereinafter.

15 In a preferred embodiment where the encoded variable filter device 111 includes
an integrating chamber 104, the source side of the spatial encoding unit 108 may be made
optically reflective and oriented in such a way that light that is blocked by the encoding
unit 108 is substantially reflected toward the integrating chamber 104. In this way, light
that passes through the variable filter 106 but blocked by the encoding unit 108 will enter
20 the integrating chamber 104 and be redirected. This light will then have a chance to pass
through another suitable portion of the filter 106 that could correspond to an open portion
of the encoding unit 108.

The order of the EVF device 111 components in Figure 2 and subsequent figures

is depicted as a light source 102, followed by a variable filter assembly 106, followed by a spatial encoding device 108. Those skilled in the art will recognize that all embodiments described herein may also be arranged with the light source 102, followed by the spatial encoding device 108, followed by the variable filter assembly 106.

5 The optical filter 106 and the encoding unit 108 may be combined into a single unit, which offers the possibility of additional encoding schemes. For example, if the encoding unit 108 comprises a MEMS device or other electromechanical system which encodes the light in such a way that the light passing through a particular encoding aperture is passing through either one of two different optical bandpass filters, then the
10 encoding unit may have half the number of encoding apertures and encoding mechanisms, and therefore require half the space. Specific embodiments of a combined filter 106 and encoding unit 108 are described in more detail hereinafter.

 The spectroscopic measurement system 100 is particularly suitable for operating in the visible or near-infrared spectral regions to measure or identify a wide variety of analytes
15 such as glucose, urea, ethanol, beta2 microglobulin, different hemoglobin types, hematocrit, other biological analytes and specific or overall tissue properties (for biometric identity applications). Other applications can include age verification, gender verification, disease state determinations, tissue hydration estimation, and sample similarity assurance. For purposes of illustration only, use of the spectrometer system 100 is described in terms of
20 measuring glucose concentration through skin tissue. An example of this application is described in U.S. Patent No. 4,975,581 to Robinson et al., the disclosure of which is hereby incorporated herein by reference. Other exemplary applications include those disclosed in U.S. Patent No. 5,494,032 to Robinson et al; U.S. Patent No. 5,596,992 to Haaland et al., the

disclosures of which are incorporated herein by reference. Further applications are disclosed in commonly assigned pending applications including U.S. Patent Application Serial No. _____, filed on the same day herewith, entitled "System for Noninvasive Measurement of Glucose in Humans"; U.S. Patent Application Serial No. 09/182,340, filed 5 October 29, 1998, entitled "Apparatus and Method for the Determination of the Adequacy of Dialysis by Non-Invasive Near-Infrared Spectroscopy" and U.S. Patent Application Serial No. 09/415,594, filed October 8, 1999, entitled "Apparatus and Method for Identification of Individuals by Near-Infrared Spectrum", the disclosures of which are each incorporated herein by reference.

10 In use, the sampler 112 is positioned adjacent the skin tissue to form a tissue interface 114. The light source 102 is then activated to pass light through the integrating chamber 104 and into the filter 106. Light having a wavelength within the acceptable bandwidth passes through the filter 106, and light of unacceptable wavelength is reflected back into the integrating chamber 104 where it is ultimately retransmitted to the filter 106.

15 Light within the acceptable bandwidth passes through the filter 106 and into encoding unit 108 which may be controlled by the computer 122. The encoding unit 108 correlates discrete locations on the filter 106 to the encoding unit 108. This can also correlate filter locations to discrete or multiple optical fibers, such that each optical fiber 110 or group of optical fibers represents or receives a specific frequency of light. Alternatively, optical

20 components such as lenses, mirrors, or light pipes can be incorporated in the system between the output of the EVF 111 and the optical fibers 110 to collect substantially all of the encoded light and redirect it into the sampler input fibers such that no specific frequency-fiber relationship exists.

The filtered light is then transmitted through the optical fibers 110 to the sampler 112, which includes input and output elements (not shown). Light is delivered into the skin tissue at the tissue interface 114 through the input element of the sampler 112. A portion of the light that is not absorbed by the tissue at the tissue interface 114 is collected by the output element of the sampler 112. The collected light is then transmitted through the detection optical fiber 116, through the lens 118, and to the detector device 120. The detector device 120 converts the light signal into an electric signal, which is representative of the non-absorbed light. The detector can be an InGaS, silicon, InSb, PbSe, Ge, Si, a bolometer or any other suitable detector and can consist of one or more detector elements. The electric signal from the detector 120 is transmitted to and processed by the computer 122 which decodes the signal and provides a measure of the analyte (e.g., glucose concentration) of interest.

It is also possible to use the raw encoded data directly for some spectroscopic measurements. This capability decreases the processing power and cost of components necessary for a stand-alone spectral system 100 and improves the response time of the system 100.

Refer now to Figures 4 and 5, which are schematic illustrations of spectrometer systems 130/140 utilizing an external light source 102. Except as described herein, the design, function and use of the spectrometer systems 130/140 are substantially the same as described with reference to the spectrometer system 100 illustrated in Figure 2. The external light source 102 may be located remotely and interfaced with the integrating chamber 104 using imaging optics 132 as shown in Figure 4, and/or non-imaging optics 142 as illustrated in Figure 5. The imaging optics 132 may comprise refractive or

reflective optics to aid in collecting and directing the light emitted by the light source 102 into the integrating chamber 104. The non-imaging optics 142 may comprise a light pipe, a fiber bundle or other similar device to transmit the light emitted by the light source 102 into the integrating chamber 104. Some types of non-imaging optical devices 142, such as a light pipe, allow the light emitted by the light source 102 to be scrambled and homogenized. An example of a suitable light pipe is disclosed in commonly assigned U.S. Patent Application Serial No. _____, filed on the same date herewith, entitled "Illumination Device and Method for Spectroscopic Analysis," the entire disclosure of which is incorporated herein by reference. Such a light pipe both spatially and angularly homogenizes light such that the system is insensitive to variation inherent in the light source which has been shown to negatively impact the predictive capability in spectroscopic analysis of tissue.

With either of the spectrometer systems 130/140 illustrated in Figures 4 and 5, respectively, the integrating chamber 104 may be of orthogonal design with smooth reflective interior sides to preserve the angularity of the light entering the integrating chamber 104. Previously disclosed shapes for the chamber can also be utilized. However, when the illumination optical fibers 116 and filter 106 are matched to apertures of the imaging/non-imaging optics 132/142, the orthogonal integrating chamber 104 is particularly beneficial because the preservation of angular characteristics maintains the desired match when light passes through the integrating chamber 104. In preferred embodiments, optical fibers which receive a preferred angular range of light are utilized to eliminate unwanted angles. Optical baffles can also be included in the output end of the integrating chamber to limit the angular distribution of the light leaving the chamber.

As mentioned previously, the filter 106 and encoding unit 108 may comprise a wide variety of designs, some of which are described with reference to Figures 6-13. Except as described herein, the design, function and use of the spectrometers systems 150/160/170/190/200/210/220 illustrated in Figures 6-13 are substantially the same as described with reference to the spectrometer system 100 illustrated in Figure 2.

Refer now to Figure 6, which is a schematic illustration of a spectrometer system 150 utilizing a rotating mask 152 encoding system. The rotary encoding mask 152 comprises a disc including a plurality of apertures 156 arranged in varying patterns in radial lines which align with selected portions of the LVF 106 at specific times when the mask 152 is rotated as shown. The position of the apertures 156 may be changed to perform the spectral encoding. Rotation of the rotary mask 152 is synchronized with the data collection system 122, and may be continuous or stepped. The bottom side 154 of the mask 152 is highly reflective to return blocked light into the integrating chamber 104 for an additional chance to pass through to the filter 106. The mask 152 may alternatively be linearly translated in order to perform the spatial encoding. Further, the mask 152 location and filter 106 order can be switched, but it would be desirable to make the mask highly reflective on both sides if placed between the source and filter.

Refer now to Figure 7, which is a schematic illustration of a spectrometer system 160 utilizing a rotating circular variable filter (CVF) encoding system 162. The CVF encoding system 162 is similar to the rotating mask 152 encoding system described above, except that the CVF encoding system 162 rotates and the illumination fibers 110 act as the aperture/mask set. In a preferred embodiment, the space around each of the fibers is filled with a reflective material that redirects the light passing through the CVF 162 back

into the integrating chamber 104 if it does not enter a fiber 110. The position of the illumination fibers 110 may be varied and the CVF 162 is rotated to perform the spectral encoding. For example, the spacing of the fibers 110 at the CVF 162 may be chosen to define a Hadamard cyclic mask. In this particular embodiment, the integrating chamber 104
5 may be cylindrically shaped as shown which will also preserve the angular characteristics of the light and could be used with the embodiments of Figure 4 and Figure 5.

Those skilled in the art will recognize that the inventive aspect of the encoding mechanism depicted in Figure 7 can also be achieved by holding the CVF 162 stationary and moving the optical fibers 110 in an appropriate manner. This same method of
10 encoding can also be applied to many of the other encoding methods described in the figures. For example, a filter assembly 106 can be combined with a set of optical fibers 110 with an additional mechanism (not shown) to move the fibers such that each fiber can be positioned to accept more or less of the light passing through a particular location of the filter assembly 106. In this way, an encoding can be implemented by varying the
15 position of each fiber separately.

Refer now to Figure 8, which is a schematic illustration of a spectrometer system 170 utilizing a liquid crystal encoding system 172 in combination with the filter 106 to produce the spectral encoding. The liquid crystal encoding system 172 comprises a liquid crystal spatial light modulator having a plurality of liquid crystal elements (not shown).
20 Each liquid crystal element of the liquid crystal encoding system 172 is individually addressed and controlled by the computer 122 to perform the encoding by individually modulating the amplitude of the light passing through each element.

Refer now to Figure 9, which is a schematic illustration of a spectrometer system 190 utilizing a digital mirror device (DMD, also known as a digital light processor or DLP) encoding system 180 in combination with the variable filter 106 to produce the spectral encoding. The DMD encoding system 180 utilizes a concave mirror 182 having a reflective surface 184 to direct light to a DMD 186. The DMD 186 comprises a plurality of individual mirrors (not shown) having reflective surfaces 188. The position of each individual mirror of the DMD 186 is controlled by the computer 122 to perform the encoding. Light reflected from the DMD 186 is either transmitted to the illumination fibers 110 through a focusing lens 189 or directed elsewhere, depending on the position of the particular DMD encoding mirror. Although not shown, the optical fibers 110, sample holder 112, detector 120, etc., are arranged the same as illustrated in Figure 2. Those skilled in the art will recognize that the DMD device and optical system shown in Figure 9 can be arranged such that light that is not transmitted to the optical fibers 110 by a particular element of the DMD 188 can be substantially reflected back through the variable filter assembly 106 and into the integrating chamber 104 resulting in additional chances for the light to pass through the system in adjacent portions of the variable filter assembly 106, thereby increasing optical efficiency. Alternatively, one or more additional samplers 112, lenses 118, and detectors 120 may be configured such that light that is reflected by a particular DMD element is being directed into one of the optical fiber bundles 110 at all times. In this way, complementary spectral data sets are generated by each of the detectors 120.

Refer now to Figure 10, which is a schematic illustration of a spectrometer system 200 utilizing optical fibers 202 with integral bandpass filters 206. Different optical

bandpass filters 206 may applied directly to each illumination fiber 202 using either conventional coating techniques or using distributed Bragg phase gratings as described by Kashyap and Raman in Fiber Bragg Gratings, Academic Press, 1999. The optical fibers 202 with integral bandpass filters 206 may be used in place of optical fibers 110 and filter assembly 106, and may be used in combination with any of the spatial encoding devices described previously to perform the encoding. For example, the optical fibers 202 with integral bandpass filters 206 may be used in combination with the mask encoder 152 described with reference to Figure 6.

Refer now to Figure 11, which is a schematic illustration of a spectrometer system 210 utilizing a micro-electromechanical systems (MEMS) encoding system 212. The leading or bottom surface 213 of the MEMS device 212 is placed in intimate contact with the active or top layer 107 of the filter 106. Alternatively, a lens or a lens array may be used to optically connect the filter 106 to the MEMS device 212. The individual elements of the MEMS device 212 may be controlled by the computer 122 to affect the optical encoding. Each of the MEMS devices 212 include an aperture 216 and optically opaque sliding door or cover 218 supported by members 214 to selectively open and close aperture 216. The apertures are preferably 10 – 1000 microns in size or diameter. As known in the art, the sliding geometry is one of many ways that multiple optical apertures can be implemented in a MEMS device.

Refer now to Figure 12, which is a schematic illustration of a spectrometer system 220 utilizing a combined filter and MEMS-based spectral encoding unit 222. Generally speaking, the filter 106 and the MEMS aperture can be combined to produce a single spectral encoding unit 222. Other aspects are substantially the same as described with

reference to MEMS device 212 illustrated in Figure 11. Each of the MEMS elements either blocks light or performs optical bandpass filtering. A very small dielectric filter 226 covers the MEMS aperture which, is then selectively opened and closed by door or cover 228 as supported by members 224. These apertures are preferably about 10 – 1000 microns in size or diameter.

Refer now to Figure 13, which is a schematic illustration of a spectrometer system 230 utilizing a MEMS double encoding system 232. Basically, the MEMS double encoding system 232 comprises the MEMS encoding unit 222 described with reference to Figure 12, but incorporates two different bandpass filters 236/238 in each encoding element, rather than an open/closed door or cover. In this way, all of the wavelengths may be addressed using half of the elements as necessary with the MEMS encoding unit 222 described with reference to Figure 12. In general, the MEMS double encoding system 232 provides a signal that is different than a Hadamard transform, but can still be practically applied to some types of analyte measurements. A simulation of the double encoding apparatus and method of Figure 13 has been generated. The data set used was a set of forearm tissue spectra that were collected on forty (40) diabetic subjects. The subjects were roughly evenly divided between Type I and Type II diabetes, were evenly divided between males and females, spanned ages from 23 years old to 67 years old, and had an ethnic composition that approximated the local population. Each subject who participated in the study was measured during two sessions per week for a total of seven weeks. Each subject had a number of capillary blood draws taken per visit, which were used in conjunction with a Yellow Springs analyzer to determine a blood glucose reference value. As well, during each visit, the subjects had four 90-second optical samples taken of their forearms using a

system based upon a Bomem WorkIR FTIR spectrometer operating at a spectral resolution of 16cm^{-1} .

The resulting FTIR data were processed in the usual way to produce 1874 intensity spectra that had significant detected intensity in the range from 4200 to 7200cm^{-1} and were approximately zero elsewhere. Standard outlier techniques based upon the spectral Mahalanobis distance and the spectral F-ratio as described by Haaland, Computer Enhanced Analytical Spectroscopy, Volume 3, Plenum Press, 1992, were applied to these data to remove outliers (127 spectra) from the data set. The resulting spectral data and their corresponding blood glucose reference values were then used to simulate the double encoding method and other related techniques.

The original intensity spectra were encoded in two ways: First, they were encoded using a simulation of a conventional Hadamard S-matrix encoding scheme using a 383×383 element transformation matrix. Second, they were encoded using a simulation of a double encoding scheme using the following procedure: the intensity spectra were trimmed slightly to 382 pixels (from 391 originally). Then a 192×192 -element Hadamard matrix was generated using the Hadamard Matlab function. This was then converted to an S-matrix by methods well known to one knowledgeable in the art. The resulting 191×191 element S-matrix was then doubled by replacing each entry that was [0] by [1 0] and each [1] entry by [0 1]. The resulting 382×382 matrix was then mapped randomly to spectral elements and then applied to the spectra. This procedure simulated a double encoding mask with random pairings of filters at each aperture.

The resulting spectral data and glucose reference values were mean-centered by patient using the method disclosed in U.S. Patent No. 6,157,041, entitled "Methods and

Apparatus for Tailoring Spectroscopic Calibration Models”, then used to perform a patient-out cross-validation for glucose values. As well, a logarithmic transform was applied to these same data, followed by a noise-scaling function that was proportional to intensity at each element, which were also mean-centered by subject and used for a subject-out cross-validation. As a comparison, the conventional S-matrix simulation data were used for cross-validation, as were data based on the original spectral intensity values. In all of these cases, the corresponding log-scaled data were also generated and used for cross-validation.

As shown in Table 1, the simulations indicated that the scaled-log of the original intensity spectra (i.e., noise scaled absorbance) produced the best result of approximately 23.3mg/dl standard error of prediction (SEP) for glucose. Next in performance, the scaled-log of the S-matrix data and the double-encoded data resulted in an SEP of approximately 25.7mg/dl in both cases. Finally, the raw spectral data, the raw S-matrix data and the raw double-encoded data all produced results of approximately 27.5mg/dl. The differences between the different data treatments that were studied were small. This similarity of results indicates that the direct use of double encoded data or the scaled-log transformation of the double encoded data is a viable option that could provide a less expensive encoding unit as well as reduced computational requirements for the spectrometer system computer.

TABLE 1: Results of Encoding Simulations

	SEP [mg/dl]: Raw Data	SEP [mg/dl]: Scaled-Logarithm of the Data
Original Spectral Data	27.5	23.3
S-Matrix Simulation Data	27.5	25.7
Double-Encoded Simulation Data	27.5	25.7

All of the spectrometer systems described thus far utilize optical fibers in one context or another. However, those skilled in the art will recognize that the spectrometer systems of the present invention may also be used without optical fibers. For example, refer now to Figure 14, which is a schematic illustration of a spectrometer system 240
5 utilizing an integrated non-fiber design. Spectrometer system 240 includes an encoding unit 242 such as a rotary mask type encoder 152 described with reference to Figure 6. Spectrometer system 240 also includes a filter 244 such as a stationary circular variable filter (CVF) that is similar to the rotating CVF device 162 described with reference to Figure 7. The encoding unit 242 and filter 244 may comprise any of the encoder/filter
10 combinations described previously.

All the light leaving the encoding unit 242 and filter 244 enters into a non-imaging optical concentrator 245 that directs the light to illuminate the tissue at the sample head 250. The optical concentrator 245 comprises a dome 247 having a reflective inner surface to direct and focus the filtered light on the sample head 250. An optical light pipe 248 or other
15 equivalent device is then used to capture the diffusely reflected light and direct it into an appropriate single-element detector 246, which can be located inside of the concentrator 245, as shown in the figure, or can be placed in a convenient position outside the concentrator, if desired, by having light pipe 248 pass through the dome 247 at some point. The detector 246 is coupled to the computer 122 as in prior embodiments. Those skilled in
20 the art will recognize that the non-fiber concepts described with reference to spectrometer system 240 may be incorporated into any of the spectrometer systems described herein. The non-fiber spectrometer system 240 described above, in addition to other non-fiber

embodiments contemplated herein, offer advantages in the terms of cost, ruggedness and/or ease of assembly.

Referring now to Figure 15, an alternative dual-chamber linear variable filter spectrometer is schematically depicted. The spectrometer system depicted in Figure 15 shows an alternative to design to the basic linear variable filter (LVF) or circular variable filter (CVF) spectrometers previously described. With the basic LVF spectrometer design, the output of the LVF is distributed spatially over a relatively large area. Adding a second LVF, in the arrangement shown, allows the light from the large LVF surface area to be efficiently collected into a smaller exit port. As with previous embodiments using the LVF and integrating chamber, it is assumed that for monochromatic light the LVF surface is highly reflective, except in the area representing the passband region for the particular wavelength of the monochromatic light.

Light from the source 102 to be analyzed goes through an entrance port 264 into the first integrating chamber 104, consisting of highly reflective walls. The front wall is of planar geometry and contains a first LVF 106. The back wall, containing the entrance port, is also planar and parallel to the front wall. The side walls may be planar, as with a polygon cross-section, or curved, as with a cylinder. Light of a specific wavelength (monochromatic) within the passband of the LVF 106, upon entering the chamber, will be reflected between the walls of the chamber until it strikes the appropriate passband region of the LVF 106 to be admitted through. Similarly, light of other wavelengths within the LVF 106 passband pass through the LVF 106 at different positions corresponding to their wavelength. Light passing through the LVF 106 is then spatially encoded by the spatial encoding device 108 and allowed to pass through a second LVF

260 with the spatial distribution of wavelength passbands matching those of the first LVF 106. This second LVF 260 is on one face of a second integrating chamber 262, similar to the first integrating chamber 104. Light passing through the second LVF 260 will reflect between the walls until a portion of it reaches the exit port 268 contained in the wall opposite the second LVF 260. The next stage can be either a single detector element or a relay system (e.g., fiber optics) to transmit the light to a tissue sampler. The integrating chambers, as described here preserve the numerical aperture (NA) of the light entering the chamber. Appropriate optics can then be added to adjust the NA before entering the input chamber and after leaving the output chamber to optimize the system for each of the components. The integrating chambers used herein may consist of a hollow chamber with reflective internal walls or of a solid block of transparent refracting material with the reflective and wavelength selective surfaces deposited on the outside walls so as to enhance and control the internal reflections.

To understand the advantage of the second LVF/integrating chamber requires defining a few quantities. Let,

A_{lvf} = total area of the face of the linear variable filter

N = number of wavelength passbands contained within A_{lvf} , i.e. the number of spectral resolution elements of the spectrometer

A_e = exit port area

for a system not containing the second LVF/integrating chamber the total area over which light must be collected is equal to A_{lvf} . This area could represent the area of a detector used to collect the signal, or it could represent the area of a fiber optic bundle used to collect the light to transport it to a sampler. For many applications, the need to collect the

light over a large area is a disadvantage. For example, the cost of a detector or the noise generated by a detector is often proportional to the detector surface area. Likewise, a large area fiber optic bundle is more costly than a small area fiber bundle.

The second LVF/integrating chamber affords a means of reducing this collection
5 area to A_e , which can be much smaller than A_{lvf} . To look at the efficiency of light transfer, we need to recognize that there are three ways a monochromatic ray of light can escape from the second chamber. First, it can go back through the LVF in the small area equal to A_{lvf}/N , representing the surface area occupied by the passband region of the LVF corresponding to the wavelength of the monochromatic ray; second, it can be
10 absorbed in the reflective walls of the integrating chamber or in the propagation medium of the chamber; or third, it can go out the exit port area A_e . If we ignore the losses due to absorption, the portion going through the exit port is equal to $A_e/(A_e + A_{lvf}/N)$. As a single example, using this equation, we see that if we make the exit port area, A_e , equal to A_{lvf}/N , we will collect 50% of the light entering the second chamber. In many cases,
15 this 50% loss would be greatly preferred over having to make a detector or fiber optic bundle N times larger in area.

From the foregoing, it should be apparent to those skilled in the art that the present invention provides a number of spectroscopic systems and spectrometers that utilize an encoder and a bandpass filter to produce a single-element multiplexing
20 spectrometer. The use of an integrating chamber further increases the SNR and system performance when it is incorporated into the system in such a way that light outside the bandpass region of the optical filter is reflected back into the integrating chamber where it is retransmitted to the filter, resulting in a significant increase in the optical power

passing through the filter. The integrating chamber essentially boosts the optical throughput of the spectroscopic system and increases the signal-to-noise ratio of the system. The integrating chamber allows direct illumination of the filter from the light source and also allows the light reflected back from the filter to make additional attempts to pass
5 through the filter. The integrating chamber maximizes the return of the reflected light to the filter assembly and minimizes optical losses.

Those skilled in the art will recognize that the present invention may be manifested in a variety of forms other than the specific embodiments described and contemplated herein. Accordingly, departures in form and detail may be made without
10 departing from the scope and spirit of the present invention as described in the appended claims.

What is claimed is:

1. A spectrometer system for performing spectroscopic determination on biological media, the spectrometer system comprising:

a light source for generating light;

an optical filter positioned to receive light from the light source, the filter having a plurality of bandpass regions, wherein light within a bandpass region is transmitted through the filter;

an optical encoding unit positioned for encoding selected frequencies of light passing through the optical filter;

a sampler for transmitting the light into the sample and for receiving the non-absorbed light from the sample; and

a detector for receiving the non-absorbed light and for generating an electric signal indicative of the non-absorbed light.

2. A spectrometer system as in claim 1, further comprising an optical filter that substantially reflects light when the incident light is of a wavelength outside the bandpass region.

3. A spectrometer system as in claim 2, further comprising an optical integrating chamber wherein light reflected from the optical filter is substantially directed into the chamber and then reflected back to the optical filter.

4. A spectrometer system as in claim 3, wherein the spectrometer system has a signal-to-noise ratio, and wherein the integrating chamber increases the signal-to-noise ratio.

5. A spectrometer system as in claim 4, wherein the integrating chamber allows direct illumination of the filter from the light source.

6. A spectrometer system as in claim 5, wherein the integrating chamber is an orthogonal design to preserve angular qualities of the light entering the integrating chamber.

7. A spectrometer system as in claim 3, wherein the light source is disposed inside the integrating chamber.

8. A spectrometer system as in claim 3, wherein the light source is disposed outside the integrating chamber.

9. A spectrometer system as in claim 1, wherein the sampler is disposed adjacent the detector.

10. A spectrometer system as in claim 1, wherein the sampler is disposed adjacent the light source.

11. A spectrometer system as in claim 1, wherein the optical filter is disposed adjacent the light source.

12. A spectrometer system as in claim 1, wherein the optical encoding unit is disposed adjacent the light source.

13. A spectrometer system as in claim 1, wherein the optical filter comprises one or more dielectric bandpass filters.

14. A spectrometer system as in claim 13, wherein the optical filter comprises a linear variable filter.

15. A spectrometer system as in claim 13, wherein the optical filter comprises a non-linear variable filter.

16. A spectrometer system as in claim 1, wherein the optical filter comprises a plurality of individual bandpass filters.

17. A spectrometer system as in claim 1, wherein the optical bandpass filters are embodied in optical fibers.

18. A spectrometer system as in claim 1, wherein the optical filter comprises a circular variable filter.

19. A spectrometer system as in claim 1, wherein the encoding unit comprises a spatial light modulator.

20. A spectrometer system as in claim 19, wherein the encoding unit comprises a rotary mask having an aperture array.

21. A spectrometer system as in claim 19, wherein the encoding unit comprises a linear translation mask having an aperture array.

22. A spectrometer system as in claim 19, wherein the encoding unit comprises a liquid crystal spatial light modulator.

23. A spectrometer system as in claim 19, wherein the encoding unit comprises a micro-electromechanical system.

24. A spectrometer system as in claim 23, wherein the individual micro-apertures are controllable to be either substantially transmissive or opaque.

25. A spectrometer system as in claim 23, wherein the individual micro-apertures are controllable to be either an optical bandpass filter or opaque.

26. A spectrometer system as in claim 23, wherein the individual micro-apertures are controllable to be one of a plurality of optical bandpass filters.

27. A spectrometer system as in claim 1, wherein the encoding unit comprises a digital mirror device.

28. A spectrometer system as in claim 1, wherein the optical filter and the encoding unit are combined into a single unit.

29. A spectrometer for use in a spectroscopic system, the spectroscopic system including a light source for generating light and a detector for receiving light, the spectrometer comprising:

an optical filter for receiving light from the light source, the filter having a plurality of bandpass regions, wherein light within a bandpass region is transmitted through the optical filter; and

an encoding unit for encoding selected frequencies of light passing through the optical filter.

30. A spectrometer as in claim 29, further comprising an optical filter that substantially reflects light when the incident light is of a wavelength outside the bandpass region.

31. A spectrometer as in claim 30, further comprising an optical integrating chamber wherein light reflected from the optical filter is substantially directed into the chamber and then reflected back to the optical filter.

32. A spectrometer as in claim 31, wherein the spectrometer has a signal-to-noise ratio, and wherein the integrating chamber increases the signal-to-noise ratio.

33. A spectrometer as in claim 32, wherein the integrating chamber allows direct illumination of the filter from the light source.

34. A spectrometer as in claim 33, wherein the integrating chamber is an orthogonal design to preserve angular qualities of the light entering the integrating chamber.

35. A spectrometer as in claim 29, wherein the optical filter is disposed adjacent the light source.

36. A spectrometer system as in claim 29, wherein the optical encoding unit is disposed adjacent the light source.

37. A spectrometer as in claim 29, wherein the optical filter comprises one or more dielectric bandpass filters.

38. A spectrometer as in claim 37, wherein the optical filter comprises a linear variable filter.

39. A spectrometer as in claim 37, wherein the optical filter comprises a non-linear variable filter.

40. A spectrometer as in claim 37, wherein the optical filter comprises a plurality of individual bandpass filters.

41. A spectrometer as in claim 40, wherein the bandpass optical filters are embodied in optical fibers.

42. A spectrometer as in claim 37, wherein the optical filter comprises a circular variable filter.

43. A spectrometer as in claim 29, wherein the encoding unit comprises a spatial light modulator.

44. A spectrometer as in claim 43, wherein the encoding unit comprises a rotary mask having an aperture array.

45. A spectrometer as in claim 43, wherein the encoding unit comprises a linear translation mask having an aperture array.

46. A spectrometer as in claim 43, wherein the encoding unit comprises a liquid crystal spatial light modulator.

47. A spectrometer as in claim 43, wherein the encoding unit comprises a micro-electromechanical system.

48. A spectrometer as in claim 47, wherein the individual micro-apertures are controllable to be either substantially transmissive or opaque.

49. A spectrometer as in claim 47, wherein the individual micro-apertures are controllable to be either an optical bandpass filter or opaque.

50. A spectrometer as in claim 47, wherein the individual micro-apertures are controllable to be one of a plurality of optical bandpass filters.

51. A spectrometer as in claim 29, wherein the encoding unit comprises a digital mirror device.

52. A spectrometer as in claim 29, wherein the optical filter and the encoding unit are combined into a single unit.

53. A spectrometer for use in selected applications of a spectroscopic system, the spectroscopic system including a light source for generating light and a detector for receiving light, the spectrometer comprising:

an optical filter for receiving light from the light source, the filter having a plurality of bandpass regions, wherein light within a bandpass region is transmitted

through the optical filter wherein said regions are sized from final regression coefficients derived from said selected application; and

an encoding unit for encoding selected frequencies of light passing through the optical filter.

54. A spectrometer for use in a spectroscopic system, the spectroscopic system including a light source for generating light and a detector for receiving light, the spectrometer comprising:

an encoding unit for encoding selected frequencies of light, said encoding unit including an array of micro-apertures, each selectively including an optical filter thereon having a selected bandpass region, wherein light received from the light source within the selected bandpass region of a particular optical filter is transmitted therethrough.

55. A spectrometer system as in claim 54, wherein the encoding unit comprises a micro-electromechanical system.

56. A spectrometer system as in claim 55, wherein the individual micro-apertures are controllable to be either an optical bandpass filter or opaque.

57. A spectrometer system as in claim 55, wherein the individual micro-apertures are controllable to be one of a plurality of optical bandpass filters.

58. A spectrometer system for performing spectroscopic determination on biological media, the spectrometer system comprising:

a light source for generating light;

a first optical filter positioned to receive light from the light source, the filter having a plurality of bandpass regions, wherein light within a bandpass region is transmitted through the filter;

an optical encoding unit positioned for encoding selected frequencies of light passing through the optical filter;

a second optical filter positioned to receive light from the optical encoding unit, the second optical filter having bandpass regions matching the first optical filter;

a sampler for transmitting the light into the sample and for receiving the non-absorbed light from the sample; and

a detector for receiving the non-absorbed light and for generating an electric signal indicative of the non-absorbed light.

59. A spectrometer system as in claim 58, further comprising a first optical integrating chamber wherein light reflected from the first optical filter is substantially directed into the chamber and then reflected back to the optical filter.

60. A spectrometer system as in claim 59, further comprising a second optical integrating chamber having an exit port operatively connected to the sampler, wherein light transmitted through said second filter which does not go through said exit port is reflected back.

61. A method for performing spectroscopic determinations on biological media, said method comprising the steps of:

collecting a set of data on an encoded variable filter spectrometer; and

applying the determination algorithm to the encoded data directly without first performing an inverse encoding step.

62. The method of claim 61, wherein said data are collected with a double-encoded spectrometer system.

Abstract of the Disclosure

Spectroscopic system and spectrometers including an optical bandpass filter unit consisting of a plurality of bandpass regions and a spatial encoding unit for encoding discrete frequencies of light passing through the optical filter. The incorporation of the
5 encoding unit allows the spectrometer system to use a detector consisting of one or a small number of elements, rather than using a more expensive detector array as is commonly used with filter-based spectrometers. The system can also include an integrating chamber that collects the light that is not transmitted through the bandpass filter unit and is substantially reflected, and redirects this light to strike the filter unit
10 again, resulting in a significant increase in the optical power passing through the filter. The integrating chamber maximizes the return of the reflected light to the filter assembly and minimizes optical losses. The integrating chamber may be an orthogonal design to preserve the optical geometric characteristics of the light entering the chamber, even after multiple reflections from the optical filter.

CERTIFICATE UNDER 37 CFR 110: The undersigned hereby certifies that this paper contains, as described hereinabove, are being deposited in the United States Postal Service "Express Mail Post Office to Addressee" having an Express Mail Mailing label number of:

EL837557669US

In an envelope addressed to:
Assistant Commissioner for Patents
Washington, DC 20231

on this 11th day of April 2001
Crompton, Seager & Tufte, LLC

By: Harold L. Boeckley

(Prior Art)




Fig. 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6




Figure 7

FIG. 8




Figure 8




Figure 9




Figure 10




Figure 11




Figure 12




Figure 13




Figure 14

COMBINED DECLARATION/POWER OF ATTORNEY FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled ENCODED VARIABLE FILTER SPECTROMETER, the specification of which (check one):

☒ is attached hereto

☐ was filed on
as U.S. Application
Serial No.

☐ and was amended on (if
applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefit(s) under Title 35, United States Code §119 (a)-(d) of any foreign application(s) for patent or inventor's certificate or of any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or of any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed:

Prior Foreign Application(s)

Number :
Country :
Day/Month/Year Filed :
Priority (yes/no) :

Number :
Country :
Day/Month/Year Filed :
Priority (yes/no) :

I hereby claim the benefit under Title 35, United States Code, §119(e) of any United States provisional application(s) as listed below:

Provisional Application No. :
Filing Date :

Provisional Application No. :
Filing Date :

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) or PCT international applications designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior application(s) in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose information that is material to patentability as defined in Title 37, Code of Federal Regulations, §1.56 and that which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

Application Serial No. :
Filing Date :
Status (patented, pending, abandoned) :

Application Serial No. :
Filing Date :
Status (patented, pending, abandoned) :

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

David M. Crompton, Reg. No. 36,772;
Glenn M. Seager, Reg. No. 36,926;
Brian N. Tufte, Reg. No. 38,638;
Robert E. Atkinson, Reg. No. 36,433; and
J. Scott Wickhem, Reg. No. 41,376.

Send correspondence to:

David M. Crompton
CROMPTON, SEAGER & TUFTE, LLC
331 Second Avenue South, Suite 895
Minneapolis, Minnesota 55401-2246
(612) 677-9050

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon, I further declare that I understand the content of this declaration.

Full name of sole or first inventor: Robert K. Rowe

Residence: 229 Ashley Lane, Corrales, New Mexico 87121

Citizenship: US

Post Office Address: 229 Ashley Lane, Corrales, New Mexico 87121

Inventor's Signature _____ Date _____

Full name of second or joint inventor: Russell E. Abbink

Residence: P.O. Box 909, Albuquerque, New Mexico 87112

Citizenship: US

Post Office Address: P.O. Box 909, Albuquerque, New Mexico 87112

Inventor's Signature _____ Date _____

Full name of third or joint inventor: Stephan P. Corcoran

Residence: 437 Alamos Road, Corrales, New Mexico 87048

Citizenship: US

Post Office Address: 437 Alamos Road, Corrales, New Mexico 87048

Inventor's Signature _____ Date _____

§ 1.56 Duty to disclose information material to patentability.

(a) A patent by its very nature is affected with a public interest. The public interest is best served, and the most effective patent examination occurs when, at the time an application is being examined, the Office is aware of and evaluates the teachings of all information material to patentability. Each individual associated with the filing and prosecution of a patent application has a duty of candor and good faith in dealing with the Office, which includes a duty to disclose to the Office all information known to that individual to be material to patentability as defined in this section. The duty to disclose information exists with respect to each pending claim until the claim is cancelled or withdrawn from consideration, or the application becomes abandoned. Information material to the patentability of a claim that is cancelled or withdrawn from consideration need not be submitted if the information is not material to the patentability of any claim remaining under consideration in the application. There is no duty to submit information which is not material to the patentability of any existing claim. The duty to disclose all information known to be material to patentability is deemed to be satisfied if all information known to be material to patentability of any claim issued in a patent was cited by the Office or submitted to the Office in the manner prescribed by §§ 1.97(b)-(d) and 1.98. However, no patent will be granted on an application in connection with which fraud on the Office was practiced or attempted or the duty of disclosure was violated through bad faith or intentional misconduct. The Office encourages applicants to carefully examine:

- (1) Prior art cited in search reports of a foreign patent office in a counterpart application, and
- (2) The closest information over which individuals associated with the filing or prosecution of a patent application believe any pending claims patentably defines, to make sure that any material information contained therein is disclosed to the Office.

(b) Under this section, information is material to patentability when it is not cumulative to information already of record or being made of record in the application, and

- (1) It establishes, by itself or in combination with other information, a *prima facie* case of unpatentability of a claim; or

- (2) It refutes, or is inconsistent with, a position the applicant takes in:

- (i) Opposing an argument of unpatentability relied on by the Office, or
 - (ii) Asserting an argument of patentability.

A *prima facie* case of unpatentability is established when the information compels a conclusion that a claim is unpatentable under the preponderance of evidence, burden-of-proof standard, giving each term in the claim its broadest reasonable construction consistent with the specification, and before any consideration is given to evidence which may be submitted in an attempt to establish a contrary conclusion of patentability.

(c) Individuals associated with the filing or prosecution of a patent application within the meaning of this section are:

- (1) Each inventor named in the application;
- (2) Each attorney or agent who prepares or prosecutes the application; and
- (3) Every other person who is substantively involved in the preparation or prosecution of the application and who is associated with the inventor, with the assignee or with anyone to whom there is an obligation to assign the application.

(d) Individuals other than the attorney, agent or inventor may comply with this section by disclosing information to the attorney, agent, or inventor.

(e) In any continuation-in-part application, the duty under this section includes the duty to disclose to the Office all information known to the person to be material to patentability, as defined in paragraph (b) of this section, which became available between the filing date of the prior application and the national or PCT international filing date of the continuation-in-part application.

[42 FR 5593, Jan. 28, 1997; paras. (d) & (e) – (i), 47 FR 21751, May 19, 1982, effective July 1, 1982; para. (c), 48 FR 2710, Jan. 20, 1983, effective Feb. 27, 1983; paras. (b) and (j), 49 FR 554, Jan. 4, 1984, effective Apr. 1, 1984; paras. (d) and (h), 50 FR 5171, Feb. 6, 1985, effective Mar. 8, 1985; para. (e), 53 FR 47808, Nov. 28, 1988, effective Jan. 1, 1989; 57 FR 2021, Jan. 17, 1992, effective Mar. 16, 1992; para. (e) added, 65 FR 54604, Sept. 8, 2000, effective Nov. 7, 2000]